

Ordering Information: To order, complete the code number below with the information
and call Precision Geothermal at (763) 479-3638 - or - email: sales@precisiongeothermal.com
GC3
Base Unit Includes:
Aluminum case Multi-Channel data logger
Depth Capacity: (max)
Piping Connection: 1 = 1" Female Cam-Lock Adaptor 2 = (Option 1) with ¾" Barbed connection 3 = (Option 1) with 1" Barbed connection 4 = (Option 1) with 1¼" Barbed connection 5 = C-Kit** (Add \$100)
Power Requirement: 1 = 240VAC / 60Hz*
Removable Extension Cord: 1 = Yes (available on 500 ft model only) 0 = No
Number of RTD's: 2 = Standard Logger - two sensors 4 = Standard Logger - four sensors (redundancy) 5 = Advanced Logger - four sensors (redundancy)
Conductivity Test Tool Kit: 1 = Yes 0 = No
H-Valve Purging Assembly: 1 = Yes 0 = No
Data Logger Configuration: 1 = Standard Data Logger (Base Configuration - no telemetry) 2 = Advanced Waterproof Data Logger 3 = Reserved
Chassis Finish: 1 = Standard Aluminum Finish 2 = Durable Anodized Aluminum Finish
GeoCube Booster Pump Option: 1 = Yes 0 = No
* Standard power ratings stated for 60Hz@240 VAC. Heating Elements adjusted for regional power standard values. Please specify your local power standards or generator output.
** C-Kit includes adapters for $\frac{1}{2}$ ", $\frac{1}{1}$ " and $\frac{1}{2}$ " pipe with quick coupling connectors for easy use.

Manufactured by:

Precision Geothermal, Inc.

5115 Industrial Street Maple Plain, MN 55359 U.S.A.

(952) 255-7050 (PHONE) (763) 479-2183 (FAX) www.precisiongeothermal.com

My Information*:

Company:				
Name:				
Address:				
City, State:				
ZIP/Postal:				
Country:				
Phone:				
Email:				
*Please note below if different shipping address needed (NO P.O. Boxes)				
International O	rders: Please select preference:	FOB	CIF	

Notes:

